





Product Service

# CERTIFICATE

No. Z1A 054168 0100 Rev. 00

Factories:



Model(s):

20 807, 20 809, 146001, 146002

Parameters:

20 807

Without quick release.

Length: 425~446 mm (40~210 N-m)

Weight without accessories: 1.1 kg

Torque scale range: 40~210 N-m

Material (H-stem): Steel

20 809

Without quick release.

Length: 425~446 mm (40~210 N-m)

Weight without accessories: 1.1 kg

Torque scale range: 40~210 N-m

Material (H-stem): Steel

Accessories: 17 mm, 19 mm sockets, 125 mm extension.

146001

Without quick release.

Length: 425~446 mm (40~210 N-m)

Weight without accessories: 1.1 kg

Torque scale range: 40~210 N-m

Material (H-stem): Steel

146002

Without quick release.

Length: 425~446 mm (40~210 N-m)

Weight without accessories: 1.1 kg

Torque scale range: 40~210 N-m

Material (H-stem): Steel

Accessories: 17 mm, 19 mm sockets, 125 mm extension.

TUV SUD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD  
ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT